



Albi Manufacturing

Division of StanChem, Inc.
401 Berlin St., East Berlin, CT 06023
Emergency Telephone Number: CHEMTREC 1-800/424-9300
Information Telephone Number: 860/828-0571
Date of Preparation: 08/28/06

Section I - Product Identification

Product Number: 16X0042
Product Name: Albi Clad FP
Product Class: Thin Film Mastic

Section II - Hazardous Ingredients

Ingredient	Percent Wt.	Occupational Exposure Limits				Skin	Vapor Pressure @20°C (mmHg)
		ACGIH TLV (mg/m ³)	ACGIH TWA (mg/m ³)	OSHA STEL (mg/m ³)	Ceiling (mg/m ³)		
Titanium Dioxide CAS #[13463-67-7]	<5	10	10	NE	NE	NE	N/A
Alkanes C6-C18 Chloro CAS #[68920-70-7]	6.65	NE	NE	NE	NE	NE	N/A

Section III - Physical Data

Boiling Range: N/A
Vapor Density: Heavier Than Air
Evaporation Rate: Slower Than Butyl Acetate
VOC Content (g/l): 21.1
Weight per Gallon: 11.5 - 12.5 #/gal.

Section IV - Fire and Explosion Hazard Data

Flammability Classification:

OSHA: Not Flammable
DOT: Not Flammable
Flash Point: N/A
LEL: N/A

Extinguishing Media: Foam Alcohol Foam CO₂ Dry Chemical Water Fog

Unusual Fire & Explosion Hazards: N/A

Special Firefighting Procedures: N/A

Section V - Health Hazard Data

Effects of Overexposure: Inhalation: May cause headaches. Skin: Possibly primary irritation. Eyes: Primary irritation.

Medical Conditions Prone to Aggravation by Exposure: Sinus and Dermatitis

Primary Route(s) of Entry: Dermal Inhalation

Section V - Health Hazard Data (cont.)

Carcinogenicity:	NTP?	Chloroalkanes - Anticipated Human Carcinogen
	IARC Monographs?	Chloroalkanes - Group 2B
	OSHA Regulated?	No
Emergency and First Aid Procedures:	Inhalation: Call a Physician. Skin: Wash thoroughly with soap and water. Remove contaminated clothing. Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, consult a physician.	

Section VI - Reactivity Data

Stability:	Stable
Hazardous Polymerization:	Will Not Occur
Hazardous Decomposition	Carbon monoxide and/or carbon dioxide may be released upon exposure to very high temperature.
Conditions To Avoid:	N/A
Incompatibility (materials to avoid):	Oxidizing agents.

Section VII - Spill or Leak Procedures

Steps to be Taken in Case Material is Released or Spilled:	Contain and remove with inert absorbent.
Waste Disposal Method:	Dispose of in accordance with local, state and federal regulations.

Section VIII - Safe Handling and Use Information

Respiratory Protection:	Approved chemical/mechanical filters designed to remove a combination of organic vapors and solid airborne particles from overspray during application.
Ventilation:	Local exhaust as required by job conditions to keep TLV below acceptable limits. Refer to OSHA regulations 29 CFR Part 1910.94.
Protective Gloves:	Recommended
Eye Protection:	Use safety eyewear with splash guards or side shields.
Other Protective Equipment:	Wear protective clothing
Hygienic Practices:	Personnel should wash thoroughly after handling product. Always wash-up before eating, smoking or using the toilet facilities.

Section IX - Special Precautions

Precautions To Be Taken in Handling and Storing:	Keep from freezing.
Other Precautions:	Avoid breathing vapors and spray mist during application.

Section X - Regulatory Information

California Prop 65 Cancer List	Alkanes, C6 - C18, Chloro
--------------------------------	---------------------------

Notice

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of StanChem's knowledge or obtained from sources believed by StanChem to be accurate. StanChem does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. For additional technical information contact StanChem.